

| | | | | |
|--|---------------|---|---|---|
| Interrupter Abbreviated Performance ⁽³⁾ | E417.29(e) | | X | |
| Operating Environment Tests: | E417.11 | | | |
| Thermal Cycling | E417.11(h) | - | X | - |
| Humidity | E417.11(g) | - | X | - |
| Acceleration | E417.11(f) | - | X | - |
| Shock | E417.11(e) | - | X | - |
| Sinusoidal Vibration | E417.11(b) | - | X | - |
| Acoustic | E417.11(d) | - | X | - |
| Random Vibration | E417.11(c) | - | X | - |
| Explosive Atmosphere | E417.11(k) | - | X | - |
| Repetitive Function | E417.29(h) | - | X | - |
| Stall | E417.29(I) | - | X | - |
| X-ray | E417.5(f) | - | X | - |
| Leakage ⁽⁴⁾ | E417.5(h) | - | X | - |
| Internal Inspection | E417.5(g) | - | 2 | - |
| Firing Tests: | E417.29(f)(1) | | | |
| High-temperature | E417.29(f)(3) | - | 2 | - |
| Low-temperature | E417.29(f)(4) | - | 2 | - |
| | I | | | |

⁽¹⁾ This test is only required for an ordnance interrupter that uses a rotor or booster charge.

⁽²⁾ A component must undergo this test before the first and again after the last operating environment test.

⁽³⁾ A component must undergo this test during each operating environment test.

⁽⁴⁾ An unsealed component that has successfully completed salt-fog, humidity, fungus resistance, and fine sand qualification tests need not undergo a leakage test.