				CCA: Test in non-normal control mode.					
2.d.5.	Engine Inoperative Trim.	±1° rudder angle or ±1° tab angle or equivalent rudder pedal. ±2° side-slip angle.	Second Segment Climb, and Approach or Landing.	This test may consist of snapshot tests.	**X**	**X**	**X**	**X**	Test should be performed in a manner similar to that for which a pilot is trained to trim an engine failure condition. 2nd segment climb test should be at takeoff thrust. Approach or landing test should be at thrust for level flight.
2.d.6.	Rudder Response.	±2°/s or ±10% of yaw rate.	Approach or Landing.	Test with stability augmentation on and off. Test with a step input at approximately 25% of full rudder pedal throw. **CCA:** Test in normal and non-normal control mode	**X**	**X**	**X**	**X**	
2.d.7.	Dutch Roll	±0.5 s or ±10% of period. ±10% of time to one half or double amplitude or ±.02 of damping ratio. ±1 s or ±20% of time difference between peaks of roll angle and side-slip angle.	Cruise, and Approach or Landing.	Test for at least six cycles with stability augmentation off. **CCA:** Test in non-normal control mode.		**X**	**X**	**X**	
2.d.8.	Steady State Sideslip.	For a given rudder position: ±2° roll angle; ±1° side-slip angle; ±2° or ±10% of aileron angle; and	Approach or Landing.	This test may be a series of snapshot tests using at least two rudder positions (in each direction for propeller-driven airplanes), one of which must be near maximum allowable rudder.	**X**	**X**	**X**	**X**	