		If alternate test is used: correct trend and ±2° aileron angle.		Test for both directions. As an alternative test, show lateral control required to maintain a steady turn with a roll angle of approximately 30°. **CCA:** Test in non-normal control mode.				
2.d.4.b.	Spiral Stability.	Correct trend and ±3° or ±10% of roll angle in 20 s.	Cruise	Airplane data averaged from multiple tests may be used. Test for both directions. As an alternative test, show lateral control required to maintain a steady turn with a roll angle of approximately 30°. **CCA:** Test in non-normal control mode.		**X**		
2.d.4.c.	Spiral Stability.	Correct trend	Cruise	Airplane data averaged from multiple tests may be used. **CCA:** Test in non-normal control mode.	**X**			
2.d.5.	Engine Inoperative Trim.	±1° rudder angle or ±1° tab angle or equivalent rudder pedal. ±2° side-slip angle.	Second Segment Climb, and Approach or Landing.	This test may consist of snapshot tests.			**X**	Test should be performed in a manner similar to that for which a pilot is trained to trim an engine failure condition. 2nd segment climb test should be at takeoff thrust. Approach or landing test should be at thrust for level flight.
2.d.6.a.	Rudder Response.	±2°/s or ±10% of yaw rate.	Approach or Landing.	For Level 7 FTD: Test with stability augmentation on and off. Test with a step input at approximately 25% of full rudder pedal throw. Not required if rudder input and response is shown in Dutch Roll test (test 2.d.7). **CCA:** Test in normal and non-normal control mode		**X**	**X**	
2.d.6.b.	Rudder Response.	Roll rate ±2°/sec, bank angle ±3°.	Approach or Landing.	May be roll response to a given rudder deflection.	**X**			May be accomplished as a yaw response test, in which case the