

TABLE XVIII: HEADLAMP UPPER BEAM PHOTOMETRY REQUIREMENTS									
TEST POINT (degrees)		UPPER BEAM #1 (UB1)		UPPER BEAM #2 (UB2)		UPPER BEAM #3 (UB3)			
		MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)		
2U	V	-	1,500	-	1,500	-	1,000		
1U	3L & 3R	-	5,000	-	5,000	-	2,000		
H	V	70,000	40,000	75,000	40,000	75,000	20,000		
H	3L & 3R	-	15,000	-	15,000	-	10,000		
H	6L & 6R	-	5,000	-	5,000	-	3,250		
H	9L & 9R	-	3,000	-	3,000	-	1,500		
H	12L & 12R	-	1,500	-	1,500	-	750		
1.5D	V	-	5,000	-	5,000	-	5,000		
1.5D	9L & 9R	-	2,000	-	2,000	-	1,500		
2.5D	V	-	2,500	-	2,500	-	2,500		
2.5D	12L & 12R	-	1,000	-	1,000	-	750		
4D	V	5,000	-	12,000	-	5,000	-		
		UPPER BEAM #4 (UB4)		UPPER BEAM #5 (UB5)		UPPER BEAM #6 (UB6)			
		MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)		
2U	V	-	750	-	750	-	1,500		
1U	3L & 3R	-	3,000	-	2,000	-	5,000		
H	V	60,000	18,000	15,000	7,000	70,000	40,000		
H	3L & 3R	-	12,000	-	3,000	-	15,000		
H	6L & 6R	-	3,000	-	2,000	-	5,000		
H	9L & 9R	-	2,000	-	1,000	-	3,000		
H	12L & 12R	-	750	-	750	-	1,500		
1.5D	V	-	3,000	-	2,000	-	5,000		
1.5D	9L & 9R	-	1,250	-	750	-	1,000		
2.5D	V	-	1,500	-	1,000	-	-		
2.5D	12L & 12R	-	600	-	400	-	-		
4D	V	5,000	-	2,500	-	5,000	-		