

**Table E.II.2. Assessment Requirements for Transmission Pipelines in HCAs (Re-assessment intervals are maximum allowed)**

Re-Assessment Requirements (see Note 3)					
Baseline Assessment Method (see Note 3)	At or above 50% SMYS		At or above 30% SMYS		Below 30% SMYS
	Max Re-Assessment Interval	Assessment Method	Max Re-Assessment Interval	Assessment Method	Max Re-Assessment Interval
Pressure Testing	7	CDA	7	CDA	Ongoing
	10	Pressure Test or ILI or DA	15 (see Note 1)	Pressure Test or ILI or DA (see Note 1)	
		Repeat inspection cycle every 10 years		Repeat inspection cycle every 15 years	
				Pressure Test or ILI or DA	
In-Line Inspection	7	CDA	7	CDA	Ongoing
	10	ILI or DA or Pressure Test	15 (see Note 1)	ILI or DA or Pressure Test (see Note 1)	
		Repeat inspection cycle every 10 years		Repeat inspection cycle every 15 years	
				Pressure Test or ILI or DA	

Preventative & Mitigative (P&M) Measures (see Table E.II.3), (see Note 2)

Pressure Test or ILI or DA

Repeat inspection cycle every 20 years

Preventative & Mitigative (P&M) Measures (see Table E.II.3), (see Note 2)

ILI or DA or Pressure Test

Repeat inspection cycle every 15 years

ILI or DA or Pressure Test