

TABLE VIII: TAILLAMP PHOTOMETRY REQUIREMENTS

GROUP NUMBER	TEST POINT (degrees)	PHOTOMETRIC INTENSITY ⁽¹⁾⁽²⁾⁽⁴⁾ (cd)						GROUP MINIMUM PHOTOMETRIC INTENSITY ⁽¹⁾⁽²⁾ (cd)							
		Lighted Sections						Lighted Sections							
		1		2		3		1	2	3					
		MINIMUM	MAXIMUM	MINIMUM	MAXIMUM	MINIMUM	MAXIMUM	MINIMUM	MAXIMUM						
1	20L	5U	0.3	18	0.5	20	0.7	25	1.4	2.4	3.5				
		5D	0.3	-	0.5	-	0.7	-							
	5L	10U	0.4	18	0.7	20	1.0	25							
		10D ⁽³⁾	0.4	-	0.7	-	1.0	-							
2	10L	5U	0.8	18	1.4	20	2.0	25	2.4	4.2	6.0				
		H	0.8	18	1.4	20	2.0	25							
	5D	5U	0.8	-	1.4	-	2.0	-							
		H	0.8	18	1.4	20	2.0	25							
3	V	5U	1.8	18	3.1	20	4.5	25	9.6	16.8	24.0				
		5L	2.0	18	3.5	20	5.0	25							
	V	5R	2.0	18	3.5	20	5.0	25							
		5D	1.8	-	3.1	-	4.5	-							
	4	10R	5U	0.8	18	1.4	20	2.0				25	2.4	4.2	6.0
			H	0.8	18	1.4	20	2.0				25			
5D		5U	0.8	-	1.4	-	2.0	-							
		H	0.8	18	1.4	20	2.0	25							
5	5R	10U	0.4	18	0.7	20	1.0	25	1.4	2.4	3.5				
		10D ⁽³⁾	0.4	-	0.7	-	1.0	-							
	20R	5U	0.3	18	0.5	20	0.7	25							
		5D	0.3	-	0.5	-	0.7	-							

(1) The photometric intensity values between test points must not be less than the lower specified minimum value of the two closest adjacent test points on a horizontal or vertical line.

(2) If the sum of intensity values for all points in the group is not less than the specified total value for the group, the measured intensity value for each individual test point is not required to meet the minimum value.

(3) Where taillamps are mounted with their axis of reference less than 750 mm above the road surface, photometry requirements below 5° down may be met at 5° down rather than at the specified required downward angle.

(4) A taillamp shall not exceed the maximum intensity at H or above.