

TABLE XIV: PARKING LAMP PHOTOMETRY REQUIREMENTS						
GROUP NUMBER	TEST POINT (degrees)	MINIMUM PHOTOMETRIC INTENSITY <sup>(1)(2)</sup> (cd)	MAXIMUM PHOTOMETRIC INTENSITY (cd)	GROUP MINIMUM PHOTOMETRIC INTENSITY (cd)		
1	20L	5U	125	2.4		
		5D	250			
	5L	10U	125			
		10D <sup>(3)</sup>	250			
		5U	125			
2	10L	H	125	3.0		
		5D	250			
	V	125				
3	5L	3.6	125	16.8		
		V	125			
	5R	3.6	125			
		V	250			
	4	10R	5D		125	3.0
			H		125	
5R		0.8	250			
		10U	125			
		10D <sup>(3)</sup>	250			
5	20R	5U	125	2.4		
		5D	250			

(1) The photometric intensity values between test points must not be less than the lower specified minimum value of the two closest adjacent test points on a horizontal or vertical line.

(2) If the sum of intensity values for all points in the group is not less than the specified total value for the group, the measured intensity value for each individual test point is not required to meet the minimum value.

(3) Where parking lamps are mounted with their axis of reference less than 750 mm above the road surface, photometry requirements below 5° down may be met at 5° down rather than at the specified required downward angle.