

TABLE XIX-a: HEADLAMP LOWER BEAM PHOTOMETRY REQUIREMENTS												
TEST POINT (degrees)		LOWER BEAM # 1M (LB1M)			LOWER BEAM # 1V (LB1V)			LOWER BEAM # 2M (LB2M)			LOWER BEAM # 2V (LB2V)	
		MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	
(¹) 10U to 90U	(¹) 90L to 90R	125	-	125	-	125	-	125	-	125	-	125
4U	8L & 8R	-	64	-	64	-	64	-	64	--	64	64
2U	4L	-	135	-	135	-	135	-	135	-	135	135
1.5U	1R to 3R	-	200	-	200	-	200	-	200	-	200	200
1.5U	1R to R	1,400	-	1,400	-	1,400	-	1,400	-	1,400	-	1,400
1U	1.5L to L	700	-	700	-	700	-	700	-	700	-	700
0.5U	1.5L to L	1,000	-	1,000	-	1,000	-	1,000	-	1,000	-	1,000
0.5U	1R to 3R	2,700	500	2,700	500	2,700	500	2,700	500	2,700	500	2,700
H	V	5,000	-	5,000	-	5,000	-	5,000	-	5,000	-	5,000
H	4L	-	135	-	135	-	135	-	135	-	135	135
H	8L	-	64	-	64	-	64	-	64	-	64	64
0.5D	1.5L to L	3,000	-	3,000	-	3,000	-	3,000	-	3,000	-	3,000
0.5D	1.5R	20,000	10,000	20,000	10,000	20,000	10,000	20,000	10,000	20,000	10,000	20,000
0.6D	1.3R	-	-	-	10,000	-	10,000	-	10,000	-	10,000	10,000
0.86D	V	-	-	-	4,500	-	4,500	-	4,500	-	4,500	4,500
0.86D	3.5L	-	-	12,000	1,800	-	1,800	-	1,800	-	1,800	1,800
1D	6L	-	1,000	-	-	-	-	-	1,000	-	-	-
1.5D	2R	-	15,000	-	15,000	-	15,000	-	15,000	-	15,000	15,000
1.5D	9L & 9R	-	1,000	-	-	-	-	-	1,000	-	-	-
2D	9L & 9R	-	-	-	1,250	-	1,250	-	1,250	-	1,250	1,250
2D	15L & 15R	-	850	-	1,000	-	1,000	-	850	-	850	1,000
2.5D	V	-	-	-	-	-	-	-	-	-	-	-
2.5D	12L & 12R	-	-	-	-	-	-	-	-	-	-	-
4D	V	7,000	-	10,000	-	10,000	-	10,000	-	10,000	-	10,000
4D	4R	12,500	-	12,500	-	12,500	-	12,500	-	12,500	-	12,500
4D	20L & 20R	-	-	-	300	-	300	-	-	-	-	300

⁽¹⁾ These test points are boundaries, intensity values within this boundary must meet the listed photometry requirement.