

TABLE XIX-b: HEADLAMP LOWER BEAM PHOTOMETRY REQUIREMENTS												
TEST POINT (degrees)		LOWER BEAM #3 M (LB3M)			LOWER BEAM #3 V (LB3V)			LOWER BEAM #4M (LB4M)			LOWER BEAM #5M (LB5M)	
		MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	
(1) 10U to 90U	(1) 90L to 90R	125	-	125	-	125	-	125	-	125	-	-
4U	8L & 8R	-	64	-	64	-	64	-	64	-	-	64
2U	4L	-	135	-	135	-	135	-	135	-	-	135
1.5U	1R to 3R	-	200	-	200	-	200	-	200	-	-	200
1.5U	1R to R	1,400	-	1,400	-	1,400	-	1,400	-	1,400	-	--
1U	1.5L to L	700	-	700	-	700	-	700	-	700	-	-
0.5U	1.5L to L	1,000	-	1,000	-	1,000	-	1,000	-	1,000	-	-
0.5U	1R to 3R	2,700	500	2,700	500	2,700	500	2,700	500	2,700	500	500
H	V	-	-	-	-	-	-	-	-	-	-	-
H	4L	-	135	-	135	-	135	-	135	-	-	135
H	8L	-	64	-	64	-	64	-	64	-	-	64
0.5D	1.5L to L	2,500	-	-	-	-	-	2,500	-	-	-	-
0.5D	1.5R	20,000	8,000	-	-	-	-	20,000	8,000	-	-	10,000
0.6D	1.3R	-	-	-	-	-	10,000	-	-	-	-	-
0.86D	V	-	--	-	-	-	4,500	-	-	-	-	-
0.86D	3.5L	-	-	12,000	1,800	-	-	-	-	-	-	-
1D	6L	-	750	-	-	-	-	-	750	-	-	1,000
1.5D	2R	-	15,000	-	15,000	-	-	-	15,000	-	-	15,000
1.5D	9L & 9R	-	750	-	-	-	-	-	750	-	-	1,000
2D	9L & 9R	-	-	-	1,250	-	-	-	-	-	-	-
2D	15L & 15R	-	700	-	1,000	-	-	-	700	-	-	850
2.5D	V	-	-	-	-	-	-	-	-	-	-	2,500
2.5D	12L & 12R	-	-	-	-	-	-	-	-	-	-	1,000
4D	V	-	-	-	-	-	-	-	-	-	-	-
4D	4R	12,500	-	12,500	-	12,500	-	12,500	-	12,500	-	7,000
4D	20L & 20R	-	-	-	-	-	300	-	-	-	-	-

(1) These test points are boundaries, intensity values within this boundary must meet the listed photometry requirement.