

TABLE XIX-c: HEADLAMP LOWER BEAM PHOTOMETRY REQUIREMENTS			LOWER BEAM # 4 V (LB4V)	
TEST POINT (degrees)		MAXIMUM PHOTOMETRIC INTENSITY (cd)	MINIMUM PHOTOMETRIC INTENSITY (cd)	
(¹) 10U to 90U	(¹) 90L to 90R	125	-	
4U	8L & 8R	-	64	
2U	4L	-	135	
1.5U	1R to 3R	-	200	
1.5U	1R to R	1,400	-	
1U	1.5L to L	700	-	
0.5U	1.5L to L	1,000	-	
0.5U	1R to 3R	2,700	500	
H	V	5,000	-	
H	4L	-	135	
H	8L	-	64	
0.5D	1.5L to L	-	-	
0.5D	1.5R	-	-	
0.6D	1.3R	-	10,000	
0.86D	V	-	4,500	
0.86D	3.5L	12,000	1,800	
1D	6L	-	-	
1.5D	2R	-	15,000	
1.5D	9L & 9R	--	-	
2D	9L & 9R	-	1,250	
2D	15L & 15R	-	1,000	
2.5D	V	-	2,500	
2.5D	12L & 12R	-	1,000	
4D	V	10,000	-	
4D	4R	12,500	-	
4D	20L & 20R	-	300	

(¹) These test points are boundaries, intensity values within this boundary must meet the listed photometry requirement.